Panel with tester for 2 batteries and activation switch Switch Code Indicator Panel →| mm 14.100.02 64x83 Analog Light toggle Black anodized aluminium 14.100.04 IP56 dual LED toggle Analog Technopolymer 75x60 14.100.05 Digital IP56 dual LED toggle Technopolymer 75x60







Digital voltmeter display

Digital touchscreen to control 2 x 12V batteries.

Code	Frame	←→ mm	
14.659.01	Dark grey	60 x 60	



Watertight electric control panel

Fitted with rubber caps. Equipped with voltmeter and battery isolator 14.385.00. Supplied with **led light check panel**. The fuses are separated on each switch. Watertight fuse holder. It requires standard glass fuses.

Code	Switches	Switches A	Fuse size mm	←→ mm
14.708.00	10	15	6x32	270x160



Watertight electric control panel with circuit breakers

Fitted with rubber caps. Equipped with voltmeter and battery isolator 14.385.00. Supplied with **LED light check panel**. The fuses are separated on each switch. Watertight fuse holder requiring standard glass fuses. Fitted with Airpax fully **automatic** circuit breakers 14.736.10/20.

Code	Switches	Switches A	← → mm
14.709.00	10	15	270x160



Electric control panel with 14 switches

Equipped with voltmeter and ammeter, and battery isolator 14.385.00. Equipped with extra bright LED light check-panel. The LEDs lights up when a switch is activated.

Code	Label	switch	Fuses	←→
			mm	mm
14.808.01*	sail yacht	15 A	6x30	327x285
14.809.00	power yacht	automatic thermo-magnetic "Airpax" 14.736.05; 14.736.10; 14.736.15; 14.736.20	-	327x285
14.809.01	sail yacht	automatic thermo-magnetic "Airpax" 14.736.05; 14.736.10; 14.736.15; 14.736.20	-	327x285

Fitted with watertight switch, coated with rubber and standard glass fuses.





14.809.00

14.808.01

AC power control panel, 220 V

Fitted with Airpax resettable automatic circuit breakers (1 x 5A, 3 x 5A, 1 x 15A) + switch LED lights + 30 m A and 25 A bipolar life saver switch + "power indicator" LED light + "polarity inversion" LED light + 0/300 V voltmeter.

Code	Magneto-thermic switches	←—→ External mm	Coupled with panel
14.810.22	5	140x285	14.809.00; 14.809.01

