



▲16.921.40/41



▲16.921.42/43

WHALE submersible pump

For suction or transfer of fresh or salt water.


Code	V	Flow l/min	Current draw A	Hose adaptor mm	Use
16.921.40	12	11	3	10/13	to be fitted into the tank
16.921.41	24	11	1.6	10/13	to be fitted into the tank
16.921.42	12	11	3	dual 10/13	in line
16.921.43	24	11	1.6	dual 10/13	in line



CARAVAN centrifugal submersible pump

Designed to be fitted into water cans.

Code	V	Flow l/min	Current draw A	Head m	Hose adaptor Ø mm
16.101.00	12	18	2	2	11




Submersible centrifugal pump

It pumps both water and diesel.

Its cylindrical shape (41-mm Ø) can be easily fitted in jerrycans and tanks.

It can turn continuously up to 20 minutes. It comes with 5-m cable and adjustable pliers.

Code	V	Flow l/min	Current draw A	Head m	Hose connector Ø mm	↔ Ø x h mm
16.105.13	12	18	4.5	10	12	175.5x41.1



Europump bilge pump

Very small bilge pump ideal for installation in confined spaces.

Code	Model	V	Max flow l/min	Current draw A	Head m	Inlet Ø mm	↔ Ø x h mm
16.613.60	300GPH	12	19	2.0	1.5	19	66x97