

Maxi pump WHALE

Made up of two combined MKV pumps; removable handle; concealed installation behind the bulkhead, fitted with trapdoor (to be ordered separately). The entry joints may be removed in order to have two separate pumps and suction from two different bilges, even if one is dry.

Code	Capacity l/m	Hose adaptor mm	Head m	mm handle excluded	Manhole	Repair kit
15.270.00	136 (with 70 turns)	38	4.5	234(h) x 292(w) x 203(d)	15.268.05	15.268.04



▲ 15.268.05

**Hand pumps****Small double-acting pump**

Suitable for extracting oil from the motor sump, or petrol, water, etc.

Code	Cc pump/capacity	Length mm
15.260.00	80	230

Bilge pumps for suction/pressing

Provide easy control of the suctioned liquid, supplied with terminal extension and special discharge spiral hose.

Code	Body length mm	Ø mm
15.263.35	390	50
15.263.55	550	50

Bilge pump for suction/pressing

Equipped with 95-cm drain tube. Ergonomic grip handle.

Code	Body length mm	Ø mm
15.265.01	390	44
15.265.02	550	44
15.265.03	1000	44

Double acting hand pump, designed to suction oil

Fitted with nylon hose for fitting onto oil sidepiece and drainage pipe; also suitable for draining needy bilges.

Code	Length mm
15.259.01	390

Manual double-acting bilge pump

Fitted with central SOFT sleeve for better intake. Drain hose cm 100.

Code	Body length mm	Ø mm
15.263.00	440	44

Bulkhead hand pump, fixed lever

For surface mounting. Compact and sturdy, made from anti-corrosion materials.

Code	Capacity l/pump cycle	Lever	Size mm	Hose adaptor mm	Spare gasket kit
15.262.20	0,33 (30 - 60 pumps/minute)	fixed	180x125x75	25	15.262.21

