

OSCULATI

Classic 360° pull-out pole

For vessels up to 20 m. Fitted with a special **AISI316 stainless steel** base. The contact is activated by inserting the pole. When the pole is removed, the clip-on cover seals the hole in order to prevent electric poles from rusting.

Version		Length cm	Light colour	Base mm	Halogen bulb included
standard	with 30° light in axis				
11.160.00	11.160.20	60	Black plastic	85x50	14.200.02 (12 V - 10 W)
11.160.01	-	60	SS	85x50	14.200.02 (12 V - 10 W)
11.160.02	11.160.22	60	White plastic	85x50	14.200.02 (12 V - 10 W)



OSCULATI

Classic 360° pull-out pole with Advance base

AISI 316

For vessels < 20 m. Made of **polished AISI316 stainless steel**, fitted with **AISI316 stainless steel base and nylon rubber**. The contact is activated by inserting the pole; when the pole is removed, the clip-on cover seals the hole.

Pole with base		Length cm	Light colour	Halogen bulb included
Standard	Flush			
11.163.00	11.163.06 New	100	Black plastic	14.200.02 (12 V - 10 W)
11.163.01	11.163.07 New	100	SS	14.200.02 (12 V - 10 W)
11.163.02	11.163.08 New	100	White plastic	14.200.02 (12 V - 10 W)
11.164.00	11.164.06 New	60	Black plastic	14.200.02 (12 V - 10 W)
11.164.01	11.164.07 New	60	SS	14.200.02 (12 V - 10 W)
11.164.02	11.164.08 New	60	White plastic	14.200.02 (12 V - 10 W)



OSCULATI

Utility 360° mooring light

Made of polycarbonate, for vessels < 20 m.

Code	Light colour	Light colour	Base Ø mm	Height mm	Halogen bulb included
11.134.00	White	Black	60	90	14.220.02 (12 V - 10 W)
11.134.02	White	White	60	90	14.220.02 (12 V - 10 W)
11.134.01	Red*	Black	60	90	14.220.04 (12 V - 15 W)



* Not Under Command.

Classic 360° LED mooring light

OSCULATI

LED

Polycarbonate and AISI316 stainless steel light. For vessels < 20-m long.

Code	Light colour	Shank for pipe fitting	Ø mm	Height mm	LED bulb included
11.133.10	Black polycarbonate	-	60	74	14.223.00 (12/24 V - 1,7 W)
11.133.11	White polycarbonate	-	60	74	14.223.00 (12/24 V - 1,7 W)
11.133.13	Black polycarbonate	INCLUDED (for 20-mm Ø tube)	60	74	14.223.00 (12/24 V - 1,7 W)
11.133.14	White polycarbonate	INCLUDED (for 20-mm Ø tube)	60	74	14.223.00 (12/24 V - 1,7 W)
11.132.10	Stainless steel	-	64	74	14.223.00 (12/24 V - 1,7 W)
11.132.11	Stainless steel	INCLUDED (for 20-mm Ø tube)	64	74	14.223.00 (12/24 V - 1,7 W)

