




▲ 20.666.xx



▲ 20.665.xx



▲ 20.666.09



▲ 20.666.xx

Chromed brass filler cap

Hidden lever opening.


Innovative system to prevent water ingress. 7-mm projection.

Code	Type	Version	Neck (D1) Ø mm	Flange (D) Ø mm	Length (H) mm
20.666.02	WATER	Straight	38	88	81
20.666.03	DIESEL	Straight	50	88	81
20.666.04	FUEL	Straight	38	88	81
20.666.09*	WASTE	Straight	38	88	115
20.665.02	WATER	Sloped at 30°	38	88	-
20.665.04	FUEL	Sloped at 30°	38	88	-

* Conforming to ISO 8099, long neck.



▲ 20.665.xx



▲ 20.666.09



▲ 20.668.01/05



▲ 20.668.21/22/23



▲ 20.668.10

Chromed brass deck filler with key

The key cover is also used as opening handle

Chromed brass deck filler with key					Chromed brass deck filler only with key without sleeve
Code	Type	Version	Neck Ø mm	Outer Ø mm	
20.668.05	FUEL	Straight	38	95	20.668.21
20.668.01	FUEL	Straight	50	95	20.668.21
20.668.03	DIESEL	Straight	50	95	20.668.22
20.668.02	WATER	Straight	38	95	20.668.23
20.668.06	WASTE	Straight	38	95	-
20.668.08	FUEL	30° angle	38	95	20.668.21
20.668.09	FUEL	30° angle	50	95	20.668.21
20.668.10	DIESEL	30° angle	50	95	20.668.22
20.668.11	WATER	30° angle	38	95	20.668.23



Chromed brass fuel deck plug

3-hole ring screw mounting. Knurled finish plug for better grip.

Code	Neck Ø mm
20.155.00	60



▲ 20.467.01



▲ 20.467.02



▲ 20.467.03

Mirror polished stainless steel deck fillers, flush mounting, fitted with opening handle

Flush mount, deck plug opening handle; fitted with safety small chain, **new version with precision-cast plug**; available with straight joint pin or 45° inclined with respect to the vertical one (to be used when the fuelling level is inclined).

Code	Type	Version	Neck Ø mm	Flange Ø mm
20.467.01	FUEL	Straight	50	80
20.467.02	WATER	Straight	38	80
20.467.03	DIESEL	Straight	50	80
20.470.00	FUEL	With 45° angled fitting	38	80
20.470.01	FUEL	With 45° angled fitting	50	80
20.470.02	WATER	With 45° angled fitting	38	80



▲ 20.470.00



▲ 20.470.01



▲ 20.470.02