

10-micron gasoline/diesel filter with disposable cartridge

Fitted with conical, self-locking and self-sealing hose adaptor.

Code	Head support	Height mm	Overhang mm	Cartridge Ø mm	Cartridge thread	Capacity l/h with pressure			10-mm fittings mm	Spare cartridge
						0.49 PSI	1.47 PSI	2.45 PSI		
17.660.40	Plastic	145	110	92	11/16"	182	315	404	INCLUDED	17.660.45
17.660.41	Aluminium	145	110	92	11/16"	182	315	404	INCLUDED	17.660.45

Equivalent Mercury 35-60494A4, 35-802893Q, 35-807172



▲ 17.660.45

**OSCULATI****Petrol filter + water/fuel separator**

Aluminium head, transparent tank, rapid drain system. Recommended for engines up to 200 HP - Equivalent to Yamaha 2W-114-00-00. Fitted with 8-mm hose adapter.

Code	Flow l/h with pressure			Total height mm	Protrusion mm	Ø mm	Spare water tray	Cartridge thread	Hose connector Ø mm INCLUDED	10-micron spare cartridge
	0.49 PSI	1.47 PSI	2.45 PSI							
17.661.30	200	316	406	230	90	75	17.661.32	13/16"	2 x 8	17.661.31

Equivalent Yamaha MAR - MINIF - IL - TR



▲ 17.661.32

Water/fuel filter/separator**OSCULATI**

Fitted with 10-micron high-capacity cartridge. Aluminium head. Universal size to fit any type of engine. Fitted with conical, self-locking and self-sealing hose adaptors, caps to close unused passages, and stainless steel clamps.

Code	Flow l/h at pressure			Cartridge micron	Recommended for	Water collection tray		Drain plug	Total height mm	Ø mm	Overhang mm	Cartridge thread	Fittings included	Spare cartridge
	0.49 PSI	1.47 PSI	2.45 PSI			Material	Spare							
17.661.35*	206	331	414	10	Petrol/ Diesel	Aluminium	-	Chromed brass	280	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.26
17.661.24	206	331	414	10	Petrol/ Diesel	Clear polyamide	17.664.12	Plastic	290	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.26
17.661.37	206	331	414	30	Diesel	Aluminium	-	Chromed brass	280	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.28

* Equivalent Yamaha MAR - FUELF - IL - TR



▲ 17.664.12



▲ 17.661.24 - Black plastic drain plug



▲ 17.661.35 - Chromed brass drain plug

Purifying filter fitted with stainless steel 120 micro filtering element

Suitable for mid power motors; made in accordance with RINA standards, suitable for diesel or petrol.

Code	Joints	Max Flow l/h (while accelerating)	Optimum flow l/h	mm	Spare filter
17.020.00	3/8"	460	240	100x100x235	17.020.01

