

Europump fresh water pumps

CISCULATI

Europump 4 low-consumption fresh water pump

 ϵ

It can feed 2 taps at the same time. Fitted with circuit breaker against overloads. It can run dry without damage.

CA

Code	Bracour	o owitch	Elow	Current	Hose adaptor	Overall	Spare	
Code			Flow I/min	draw A	Ø mm	dimensions	pressure	
	version	calibrated at	1/111111	uraw A	Ø	mm	switch	
16.503.12	automatic	2,8 BAR/40 PSI	3.8	2.6	10	170x100x60	16.540.01	





Europump 4 New Generation fresh water pump

.. 3. €

It can serve two outlets. Overload protection. It can run dry without getting damaged. IP54 watertight. Self-priming up to 1.5 metres. Pulsation-dampening bypass system.

Code	V	Flow I/min	Current draw A	Working pressure bar	Snap hose mm
16.501.12	12	5.6	4.5	2.8	10





OSCULATI



Europump 3-diaphragm self-priming fresh water pump



It can run dry without damage, no vibrations, very quiet. Fitted with internal bypass for inlet pressure control. Permanent magnet motor with self-lubricating shaft. Circuit breaker against unwanted overheating.

4 plug-in fittings (2 x 1/2" threads + 1 x 14-mm straight hose adaptor + 1 x 14-mm 90° hose adaptor) and plug-in inlet strainer,

Code	Type	٧	Flow	Current	Operating	←→ mm						
			l/min	draw A	pressure bar	Α	В	С	D	E	F	G
16.509.12	Europump "8"	12	8	5	2	110	106	77	98	240	85	59
16.510.12	Europump "11"	12	11	6	3	110	106	77	98	240	85	59

16.540.03 Spare pressure switch for 16.509.12 **16.540.04** Spare pressure switch for 16.510.12

16.533.01 Spare filter





Europump 4-diaphragm self-priming fresh water pump



It can run dry without damage, no vibrations, very quiet.

CA

Fitted with internal bypass for inlet pressure control. Permanent magnet motor with self-lubricating shaft.

The 4-diaphragm system prevents the pulsations that usually occur in the other fresh water pumps with a semi-open tap.

4 plug-in fittings ($2 \times 1/2$ " threads and 2×14 -mm with 1/2" hose adaptors) and a plug-in inlet strainer.



Code	Туре	V	Flow I/min	Current draw	Operating pressure	←→ mm	Spare parts		
				Α	bar		Pressure switch	Filter	
16.512.12	Europump 12	12	12.5	4	2.45	213x105x95	16.540.01	16.533.01	
16.512.24	Europump12	24	12.5	2	2.45	213x105x95	16.540.01	16.533.01	
16.517.12	Europump 18	12	17	6	2.80	257x105x95	16.540.02	16.533.01	
16.517.24	Europump 18	24	17	2.5	2.80	257x105x95	16.540.02	16.533.01	