

Atria LED ceiling light for recess mounting

IP40/65

AISI 304

Stainless steel body. Satin-finish diffuser. Double mounting system: hidden screws or stainless steel internal springs.


Code	Finish	V	W	Switch	IP Degree	Lumen	K	LED beam angle	No of LEDs	Light colour
13.447.01	Mirror-polished	12/24	2	No	IP65	215	3000	100°	12 LED SMD G4	<input type="checkbox"/> White
13.447.02	Mirror-polished	12/24	2	Yes	IP40	215	3000	100°	12 LED SMD G4	<input type="checkbox"/> White
13.447.04	Nickel satin-finish	12/24	2.4	No	IP65	215	3000	100°	12 LED SMD G4	<input type="checkbox"/> White
13.447.05	Nickel satin-finish	12/24	2.4	Yes	IP40	215	3000	100°	12 LED SMD G4	<input type="checkbox"/> White
13.447.21	Mirror-polished	12/24	8.4	No	IP65	500	3000	60°	3x3 LED HD	<input type="checkbox"/> White



▲ 13.447.01



▲ 13.447.02



▲ 13.447.21

Atria halogen ceiling light for recess mounting

IP40/65

AISI 304

Stainless steel body. Satin-finish glass diffuser. Double mounting system: hidden screws or stainless steel internal springs.


Code	Finish	V	W	Switch	IP Degree	Bulb	Spare bulb	Light colour
13.447.90	Mirror-polished	12	10	no	IP65	G4	14.454.12; 14.454.24	<input type="checkbox"/> white
13.447.91	Mirror-polished	12	10	yes	IP40	G4	14.454.12; 14.454.24	<input type="checkbox"/> white



▲ 13.447.90



▲ 13.447.91


**Aruba reduced recess fit LED ceiling light**

IP56

AISI 316

Technopolymer body and polished AISI316 stainless steel finishing ring. Polycarbonate opal lens. Mounting with stainless steel springs (no screws).


Code	Finish	V	W	Switch	Lumen	K	LED beam angle	No of LEDs	LED colour	mm
13.444.01	SS	12/24	3	No	193	3000	120°	14	<input type="checkbox"/> White	Ø 72.3 x 21.8
13.444.02	SS	12/24	3	Touch	193	3000	120°	14	<input type="checkbox"/> White	Ø 72.3 x 21.8
13.444.11	SS	12/24	3	No	193	3000	120°	14	<input type="checkbox"/> White	72.4 x 72.4 x 21.8
13.444.12	SS	12/24	3	Touch	193	3000	120°	14	<input type="checkbox"/> White	72.4 x 72.4 x 21.8



▲ 13.444.01/02



▲ 13.444.01/02



▲ 13.444.11/12



▲ 13.444.11/12


Montsarrat LED ceiling light for recess mounting

IP65

AISI 304

White epoxy-powder coated aluminium body, stainless steel finish ring.

Code	Finish	V	W	lumen	K	LED beam angle	No. of LEDs	Light colour
13.445.11	Mirror-polished	12/24	8	500	3000	120°	3 LED HD	<input type="checkbox"/> white

**Asterope halogen ceiling light for recess mounting**

IP40

AISI 304

Glass diffuser, dichroic parabolic reflector.

Code	Finish	V	W	Bulb	Spare bulb	Light colour
13.434.01	mirror-polished	12	20	G4	14.453.01; 14.100.24	<input type="checkbox"/> white
13.434.02	golden	12	20	G4	14.453.01; 14.100.24	<input type="checkbox"/> white

OSCULATI

▲ 13.434.01



▲ 13.434.02

