









Blade fuse holder, waterproof

Semi built-in box with rubber seal, housings for 10 blade fuses, rear outlet, 6 spare fuses, LED light for burnt out fuses.

Code	Volt	No of outlets	Max A for each outlet	mm
14.100.65	12/24	10	25	125x90



Fuse holder box for small fuses

Flame-retardant black PBT case and clear polycarbonate cover. Tin-plated copper blade contacts, 6.3-mm standard size.



Warning LED light in case of interrupted fuse.

Code	V	No. of outputs	Max capacity A per single fuse	Max capacity A	mm
14.101.04	12/24	4	25	100	85x47x35 H
14.101.06	12/24	6	25	100	85x63x35 H
14.101.10	12/24	10	25	100	85x95x35 H

Fuse holder box with warning lights

For standard lamellar fuses. Equipped with LED warning light for cut off fuse.

Code	Fuse housing	Warning LED	Max total capacity A	Max capacity for single fuse	mm			
					A	B	C	D
14.102.70	4	4	100	30	47	85	36	63
14.102.71	6	6	100	30	63	85	36	63
14.102.72	10	10	100	30	95	85	36	63



OSCULATI

Fuse holder box with transparent snap cover, made of polycarbonate

Silver-plated phosphor bronze connections. It fit regular lamellar fuses.

Admissible voltage: 12/24 volt.

Total max amperage of the box: 100 Amps.

Max amperage for each fuse: 20 Amps.

2 spare fuse holders on the cover.

Version for standard fuses	Version for resettable fuses 14.005.xx or similar (ETA, COOPER, etc.)	Fuse housing	Contacts (-)	(-) Common	(+) Common	mm
14.183.06	14.183.26	6	6	1	1	125x85
14.183.12	14.183.32	12	12	1	1	165x85

Complete with 6/12 writable stickers to mark the single uses



OSCULATI

High-capacity fuse holder

Made of thermoplastic with removable clear cover.

Code	Base mm	For fuses
14.100.41	95x42	ANL 14.100.xx
14.099.41	95x42	MEGA 14.099.xx

