

OSCULATI

Vertical 5-hole level sensor with S5 flange
WATER+FUEL

Ideal for either fuel or water . Any length available for a minimum order of 10 pieces. 12/24 V compatible. 316 stainless steel.

Resistance 240/33 Ω*	Resistance 10/180 Ω**	Length cm
27.160.15	27.161.15	15
27.160.17	27.161.17	17
27.160.20	27.161.20	20
27.160.22	27.161.22	22
27.160.25	27.161.25	25
27.160.28	27.161.28	28
27.160.30	27.161.30	30
27.160.32	27.161.32	32
27.160.35	27.161.35	35
27.160.36	-	36
27.160.38	-	38
27.160.40	27.161.40	40
27.160.45	27.161.45	45
27.160.47	-	47
27.160.48	-	48
27.160.50	27.161.50	50
27.160.53	-	53
27.160.55	27.161.55	55
27.160.58	-	58
-	27.161.59	59
27.160.60	27.161.60	60
27.160.63	-	63
27.160.65	27.161.65	65
27.160.70	27.161.70	70
27.160.80	27.161.80	80
27.160.90	27.161.90	90
27.160.10	27.161.10	100
27.160.11	27.161.11	110
27.160.12	27.161.12	120

* For instruments: Teleflex, Aqua Meter, Vetus, S. Giorgio Sein (Veglia), Beede, Medallion, Datcom, 27.160.00, models Taiwan - Wena, Osculati.

** For instruments: Yazaki, mod. 3 wires, Faria Europa, VDO, Uflex, Guardian.

OSCULATI

Level sensor with NMEA 2000 outlet signal

SAE 5-bore international flange. 12/24V compatible. IP65 watertight. **Stainless steel** body.

Level sensors are programmed to indicate the **use** of the tank (ex. black/grey/freshwater - fuel) and, if communicated when ordering the items, the **volume** that will be expressed in litres instead of in percentage. In case more than one tank for the same liquid is present onboard, the order shall also indicate the **numbering of the tanks** (ex. 1 - 2 - 3).

Version				Length mm
Fuel	Water	Grey water	Black water	
27.165.15	27.166.15	27.167.15	27.168.15	150
27.165.17	27.166.17	27.167.17	27.168.17	170
27.165.20	27.166.20	27.167.20	27.168.20	200
27.165.22	27.166.22	27.167.22	27.168.22	225
27.165.25	27.166.25	27.167.25	27.168.25	250
27.165.28	27.166.28	27.167.28	27.168.28	275
27.165.30	27.166.30	27.167.30	27.168.30	300
27.165.35	27.166.35	27.167.35	27.168.35	350
27.165.40	27.166.40	27.167.40	27.168.40	400
27.165.45	27.166.45	27.167.45	27.168.45	450
27.165.50	27.166.50	27.167.50	27.168.50	500
27.165.55	27.166.55	27.167.55	27.168.55	550
27.165.60	27.166.60	27.167.60	27.168.60	600
27.165.65	27.166.65	27.167.65	27.168.65	650
27.165.70	27.166.70	27.167.70	27.168.70	700
27.165.80	27.166.80	27.167.80	27.168.80	800
27.165.90	27.166.90	27.167.90	27.168.90	900
27.165.99	27.166.99	27.167.99	27.168.99	1000

OSCULATI

Vertical level sensor with S3 threaded flange
WATER+FUEL

Ideal for either fuel or water. Any length available for a minimum order of 10 pieces. 12/24 V compatible. AISI316 stainless steel.

Resistance 240/33 Ω*	Resistance 10/180 Ω**	Length cm
27.170.17	-	17
27.170.20	27.171.20	20
27.170.22	-	22
27.170.25	27.171.25	25
27.170.28	27.171.28	28
27.170.30	27.171.30	30
27.170.35	27.171.35	35
27.170.40	27.171.40	40
27.170.45	-	45
27.170.50	-	50

* For instruments: Teleflex, Aqua Meter, Vetus, S. Giorgio Sein (Veglia), Beede, Medallion, Datcom, 27.160.00, Taiwan-Wena and Osculati models.

** For instruments: Yazaki, mod. 3 wires, Faria Europa, VDO, Uflex, Guardian.