

Cuerpo y base inox 304.  
Lentes acrílicas.

Manufactured in 304 SS top  
and base.

Corpo e base inox 304. Lente  
acrilica.

Corps et base inox 304.  
Lentille acrylique.

| REF     |  |  |  |  |  |
|---------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|         |                                                                                   |                                                                                   | (mm)                                                                              |                                                                                   |                                                                                   |
| GS10321 | 12 m                                                                              | 12V                                                                               | 76 x 37                                                                           | 600 mm                                                                            | 1                                                                                 |
| GS10318 | 12 m                                                                              | 12V                                                                               | 76 x 37                                                                           | 600 mm                                                                            | 1                                                                                 |

**GOLDENSHIP**



Cuerpo y base de plástico.  
Lentes acrílicas.  
Tubo y base de acero inox.

Manufactured in plastic with  
acrylic lense.  
Pole and base in stainless  
steel.

Corpo e base in plastica,  
Lente acrilica.  
Tubo e base in acciaio inox.

Feu LED corps et base en  
plastique, lentille acrylique,  
tube et base en inox.

| REF     | REF  |  |  |  |  |  |  |
|---------|------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|         |      |                                                                                   |                                                                                   | (mm)                                                                              | (mm)                                                                              |                                                                                   |                                                                                   |
| GS10325 | 12 m | 12V                                                                               | 76 x 37                                                                           | 530                                                                               |                                                                                   |                                                                                   | 1                                                                                 |
| GS10334 | 12 m | 12V                                                                               | 60 x 48                                                                           | 530                                                                               | 2M/ NM                                                                            |                                                                                   | 1                                                                                 |
| GS10335 | 12 m | 12V                                                                               | 60 x 48                                                                           | 600                                                                               | 2M/ NM                                                                            |                                                                                   | 1                                                                                 |
| GS10353 | 12 m | BA15d<br>12V 10W                                                                  | 60 x 48                                                                           | 1000                                                                              | 2M/ NM                                                                            |                                                                                   | 1                                                                                 |

**GOLDENSHIP**



Desmontable.  
Cuerpo de plástico, tubo de  
acero inox pulido.  
Base de plástico con enchufe.

Stow-A-Way plug-in pole  
light. Nylon body with clear  
lens and stainless steel tube.  
Plastic base with socket and  
cover.

Smontabile.  
Corpo in plastica, tubo in  
acciaio inox.  
Base in plastica con spina  
e coperchio.

Feu sur mât enfichable  
Corps en nylon avec lentille  
transparente et tube en  
inox. Base en plastique avec  
douille et couvercle.

| REF             | REF |  |  |  |  |  |  |  |
|-----------------|-----|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                 |     |                                                                                     |                                                                                     |                                                                                     | (mm)                                                                                | (mm)                                                                                |                                                                                     |                                                                                     |
| GS10114         | 0°  | 12V 5W                                                                              |                                                                                     |                                                                                     |                                                                                     | 570                                                                                 |                                                                                     | 1                                                                                   |
| GS10111         | 16° | Ba15d 12V<br>10W                                                                    |                                                                                     |                                                                                     | 65 x 43                                                                             | 530                                                                                 | 2nm                                                                                 | 1                                                                                   |
| GS10348 GS10349 | 16° | Ba15d 12V<br>10W                                                                    |                                                                                     |                                                                                     | 65 x 43                                                                             | 600                                                                                 | 2nm                                                                                 | 1                                                                                   |
| GS10322 GS10324 |     |                                                                                     | 12 V                                                                                |                                                                                     | 65 x 43                                                                             | 600                                                                                 | 2nm                                                                                 | 1                                                                                   |
| GS10323         |     |                                                                                     | 12 V                                                                                |                                                                                     | 65 x 43                                                                             | 1300                                                                                | 2nm                                                                                 | 1                                                                                   |
| GS10336         | 16° | 12V                                                                                 | 12m                                                                                 |                                                                                     | 83 x 41                                                                             | 530                                                                                 |                                                                                     | 1                                                                                   |
| GS10337         | 16° | 12V                                                                                 | 12m                                                                                 |                                                                                     | 83 x 41                                                                             | 600                                                                                 |                                                                                     | 1                                                                                   |

**GOLDENSHIP**



Desmontable.  
Cuerpo de policarbonato.  
Ajustable hasta 40° para  
adaptarse al alineamiento  
horizontal sin importancia de  
la configuración de la base.  
Tubo de aluminio anodizado.  
Para bases: GS10116,  
GS10117, GS10118,  
GS10119

Stow-A-Way plug-in pole  
light.  
Polycarbonate body with  
clear lens and anodized tube.  
Adjustability of the globe  
allows for proper horizontal  
alignment regardless of base  
configuration.  
For bases: GS10116,  
GS10117, GS10118,  
GS10119

Smontabile.  
Corpo in policarbonato.  
Pieghievole fino a 40° per  
adattarsi all'allineamento.  
Tubo in alluminio anodizzato.  
Per basi : GS10116,  
GS10117, GS10118, GS  
10119

Amovible.  
Corps en polycarbonate.  
Pliable jusqu'à 40° pour  
s'adapter à l'alignement.  
Tube en alu anodisé.  
Pour les bases: GS10116,  
GS10117, GS10118,  
GS10119

| REF     |  |  |  |  |
|---------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|         |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| GS10104 | 20 m                                                                                | 12V                                                                                 | 900 mm                                                                              | 1                                                                                   |
| GS10105 | 20 m                                                                                | 12V                                                                                 | 1200 mm                                                                             | 1                                                                                   |

**PERKO®**

