

ELEVADOR DE
ESCOTILLAS

Cilindro electromecánico para abrir y cerrar escotillas, tapas de motor, etc.
Eje de acero inox.
Puede elevar hasta 226 kg.
Alimentación 12V.

ELECTRIC HATCH LIFTS

Electromechanical actuator made of non corrosive materials and completely sumersible.
Stainless steel ram.
Up to 498 lbs lift.
Operation: 12V.

PISTONE SPORTELLI
ELETTROMECCANICO

Pistone elettromeccanico per aprire e chiudere le botole, coperchi motore etc.
Asse in acciaio inox. Solleva fino a 226 kg. Alimentazione 12V

VERINS DE CAPOT
ELECTRIQUES

Vérin électromécanique pour ouvrir et fermer les trappes, les capots moteur, etc.
Axe en inox. Soulève jusqu'à 226 kg. Alimentation 12V

REF	RECOGIDO RETRACTED DIMENSIONI FERME	EXTENDIDO EXTENDED ESTENSIONE OUVERT	RECORRIDO STROKE CORSO COURSE
LENHL400	38 cm	48 cm	10 cm
LENHL800S	53 cm	74 cm	20 cm
LENHL800	64 cm	84 cm	20 cm
LENHL1200S	64 cm	94 cm	30 cm
LENHL1200	74 cm	104 cm	30 cm
LENHL1600S	74 cm	114 cm	40 cm
LENHL1600	84 cm	124 cm	40 cm
LENHL2000S	84 cm	134 cm	50 cm
LENHL2000	94 cm	145 cm	50 cm
LENHL2400S	94 cm	155 cm	60 cm
LENHL2400	104 cm	165 cm	60 cm
LENHL2600	120 cm	185 cm	66 cm
LENHL3000	120 cm	195 cm	76 cm



INTERRUPTOR ELEVADOR DE ESCOTILLAS
HATCHLIFTS SWITCHES
INTERRUTTORE ELEVATORE
INTERRUPTEUR POUR VERIN DE LEVAGE

REF
LEN10225



TAPA DE REGISTRO INSPECTION PLATE TAPPO DI ISPEZIONE TRAPPE DE VISITE

Termoplástico ABS antienviejamiento y resistente a los rayos ultravioleta con refuerzo robusto.

Anti-Aging,
Ultraviolet-Resistant ABS
Thermoplastic with robust reinforcement.

Termoplastico ABS anti-invecchiamento, resistente agli ultravioletti con robusto rinforzo.

Thermoplastique ABS anti-âge, résistant aux UV avec renfort robuste.

REF	Ø INT (mm)	Ø EXT (mm)
SFRH100401	101	143
SFRH100601	151	198
SFRH100801	180	250

SEAFLO



Cierre hermético a rosca con aro tórico.
Base de plástico blanco.
Tapa transparente de ABS.
Resistente a los rayos U.V.

Screw-on inspection cover watertight with O-ring seal.
White base and clear ABS cover.

Chiusura ermetica a filetto con o-ring. Base in plastica bianca. Tappo trasparente in ABS resistente ai raggi UV.

Fermeture filetée étanche à l'air avec joint torique. Base en plastique blanc. Capuchon transparent en ABS résistant aux UV.

REF	Ø INT	Ø EXT	
GS31295	102 mm	145 mm	1
GS31296	127 mm	165 mm	1
GS31297	152 mm	200 mm	1

GOLDENSHIP



Cierre hermético a rosca con aro tórico.
Fabricada en plástico resistente a los rayos U.V.
Color blanco.

Screw-on inspection cover watertight with O-ring seal.
U.V. stabilized plastic.
White.

Chiusura ermetica a filetto con o-ring.
In plastica resistente ai raggi UV. Colore bianco.

Fermeture filetée, hermétique avec joint torique. Fabriqué en plastique résistant aux UV. Couleur blanche.

REF	Ø INT	Ø EXT	
GS31290	102 mm	145 mm	1
GS31291	127 mm	165 mm	1
GS31292	152 mm	200 mm	1

GOLDENSHIP

