Quick coupling kit for stainless steel ladders

Code	Description			
49.560.00	To turn ladders 49.566.03, 49.566.04, 49.566.05, 49.572.03, 49.572.04, 49.572.05, 49.582.03, 49.582.04, 49.582.05 into removable ladders. It consists of 2 plates + two brackets. Suitable for any ladder with 22-mm tube.			



Foldable ladders wall-mounting

AISI 316

Made of mirror polished **stainless steel**, designed for stern mounting, fitted with oval steps; these type of steps are smoother and more comfortable than traditional rounded steps; the upper steps are coated with a anti-skid plastic material.

Code	Type of ladder	Steps	Length mm	Width mm	Centre distance mm
49.572.03	Standard	3	630	260	240
49.572.33*	Narrow	3	630	220	200
49.573.03*	Very narrow	3	630	180	160
49.572.04	Standard	4	900	260	240
49.572.05	Standard	5	1150	260	240

^{*} Specially designed for rubber dinghies.







Foldable ladder with arch mounting arms

AISI 316

Made of mirror polished **stainless steel**, fitted with arch mounting arms, made for an easier climb; oval steps, these type of steps are smoother and more comfortable than traditional rounded steps; the upper part of the steps is coated with a anti-skid plastic material.

Code	No. of steps	Length mm	Width mm	Centre-to-centre mm
49.582.03	3	670	260	240
49.582.04	4	910	260	240
49.582.05	5	1150	260	240



Telescopic ladder for fixing under the gangplank

AISI 316

Made of mirror-polished stainless steel. Oval steps with with plastic foot board.

Code	Steps	Tube Ø	Length mm		Max width
		mm	Extended	Retracted	mm
49.542.03	3	19/25/31	880	370	300







OSCULATI

