

ENCENDEDOR DE PANEL

CHARTLIGHT/LIGHTER

PRESA ACCENDISIGARI

PRISE ALLUME CIGARE

Encendedor con luz de cartas incorporada. Construido en acero inox.

Stainless steel chartlight and cigarette lighter.

Presa accendisigari con luce. In acciaio inox.

Prixe allume-cigare avec lumière. En acier inoxydable.

REF			
GS11050	12V	1	

GOLDENSHIP



CONECTOR DOBLE

DOUBLE POWER OUTLET

SDOPPIATORE ALIMENTAZIONE

PRISE DOUBLE

Convierte cualquier enchufe de encendedor de panel en toma de alimentación de 12 V doble. No utilizar con encendedores.

Converts any 12V cigarette lighter socket to dual power outlet. No use with lighter.

Converte qualunque spina di accensione del pannello con alimentazione a 12V doppio. Non usare con spine.

Convertit n'importe quelle prise allume-cigare 12V en double prise de courant. Ne pas utiliser comme allume-cigare.

REF			
GS11010	12V	1	

GOLDENSHIP



BASE CON PROTECTOR

POWER OUTLET

PRESA DI CORRENTE

PRISE 12V

Para montar en paredes o techos. No utilizar con encendedores.

Suitable for wall or ceiling mounting.

Da montare in parete. Non utilizzare con spine.

A monter sur une cloison. Ne pas utiliser comme allume-cigare.

REF			
GS11007	80 x 65 x 63 mm	1	

GOLDENSHIP



BASE CONEXION USB

USB CHARGER SOCKET

BASE CONNESSIONE USB

BASE CONNEXION USB

Base de panel para carga doble de USB. Salida de corriente máxima: 2,1 A DC (total)

Socket base for 12V. to dual USB port chargers. Max output current: 2,1 A DC (total)

Base doppia per caricatore USB. Uscita di corrente massima 2,1 A DC (total)

Base double pour chargeur USB. Sortie de courant maxi 2,1 A CC (total)

REF	IN	OUT	
BS1016	12V	5V ±5%	1
BS1045	12/24 V	5V ±5%	1

BLUE SEA SYSTEMS



BS1016



BS1045

Base de panel para carga doble de USB.

Socket base for 12V. to dual USB port chargers.

Base doppia per caricatore USB.

Base double pour chargeur USB.

REF	LED	IN	OUT	
AM12VDUSB	✓	12/24V DC	2,1A 5V	48,5 x 43,1 mm 1

MARINCO



REF	IN	OUT	
BS1478	12V	5V ±5%	1

BLUE SEA SYSTEMS

REF	IN	OUT	
GS11011	12/24V DC	2,1A 5V ±5%	Ø33,3 mm x 49,7 mm 1
GS11012	12/24V DC	3,4A 5V ±5%	Ø33,3 mm x 49,7 mm 1

GOLDENSHIP



GS11012

GS11011