



Europump combined fresh water pump and accumulator tank



The system includes a 4-diaphragm fresh water pump fitted with a 1-litre stainless steel accumulator tank and an inlet strainer.
280x260-mm base made of sturdy ABS size.
Mounting by means of 4 vibration-damping grommets.
1/2" inlet fittings or 14-mm hose adaptors. 1/2" female outlet fitting.

Code	V	Flow l/min	Installed fresh water pump	SS tank
16.506.03	12	12	Europump 16.512.12	16.126.01

Europump Washdown pump for deck washing



It combines a fresh water pump 16.517.12/24 fitted with strainers and a trigger nozzle 36.189.00 + 36.189.01 + 36.189.02.
Ideal for washing decks, bilges, anchors, sterndrive units and propellers.
Strainer and 4 fittings.

Code	V	Spare parts	
		pressure switch	filter
16.520.12	12	16.540.02	16.533.01
16.520.24	24	16.540.02	16.533.01



Washdown kit

It includes:

- 1 x high-pressure 4.2-bar 5-diaphragm fresh water pump.
- 1 x strainer.
- 1 x trigger nozzle.
- 2 x 12-mm hose adaptors.
- 1 x 7.5-m self-coiling hose.

It also works with salt water.

Code	V	Flow l/min	Current draw A	Pressure bar
16.521.12	12	21.18	17	4.8
16.521.24	24	21.18	10	4.8

OSCULATI



Europump 4-diaphragm self-priming bilge pump



It can run dry without damage. Also ideal as drain pump for **grey water** tanks.
Strainer + 4 fittings (2x1/2" threads + 2x14-mm with 1/2" hose adaptor).

Code	V	Flow l/min	Current draw A	Mounting top level	mm	Spare filter
16.525.12	12	17	9.2	up to m 1.80 above the level	240x105x95	16.533.01
16.525.24	24	17	5.6	up to m 1.80 above the level	240x105x95	16.533.01



OSCULATI



Europump water circulation pump



Used in heat exchangers, fridge systems and air cooling systems.
Ideal as delivery pump for watermakers.
Silent, low consumption. **Strainer + 4 fittings.**

Code	V	Flow l/min	Current draw A	mm	Spare filter
16.530.12	12	6	1.2	200x105x95	16.533.01
16.530.24	24	6	0.6	200x105x95	16.533.01

