12/24V USB plugs

UBS connection to plug into standard current/lighter sockets.

Code	Description	V	Fuse + LED activation
14.517.09	Double USB 2.5 A. For standard current plugs (type 14.517.01, 14.518.00, 14.517.08)	12/24	Yes
14.517.15	Double USB with watertight cap (5V/2.1A)	12/24	Yes

Extension spiral cable

14.507.00 3.60-m version with double male/female plug (lighter type). Suitable for socket type **14.519.10; 14.519.12** and **13.008.00**, on the other side portable phones, lights, etc.

Digital voltmeter/ampere meter and sockets for recess mounting

With or without front panel.

Code	8/32V digital voltmeter	0/10A digital ammeter	Power outlet	Dual USB plug	A	Version
14.517.20	x					For recess fit
14.517.21	x		x			For recess fit
14.517.42	x			x	2.4 + 2.4	For recess fit
14.517.43	x		x	x	2.4 + 2.4	For recess fit
14.517.25	x	x				For recess fit
14.517.26	x	x	x			For recess fit
14.517.28	x	x	x	x	2.1 + 1.0	For recess fit

SCANSTRUT Flip Pro USB-A and USB-C watertight sockets

Ultra-fast dual USB port (large and small) charger. IPX4 waterproof with the cover closed. Supercompact footprint, it will charge up to 2 devices at a time.
Powerful charge (36W/12V - 60W/24V).

Code	V	Max current A	Mounting hole-Ø mm
14.195.80	12/24	6	29