

OSCULATI



## High-strength eye-spliced fender line

Polyester double braid with **hand-spliced eye**.

White	Blue	Black	Ø mm	Length m
06.444.46	06.444.59	06.444.54	6	1.5
06.444.50	06.444.60	06.444.55	8	1.5
06.444.51	06.444.61	06.444.56	10	2
06.444.52	06.444.62	06.444.57	12	2.5



## Reels of high-strength polypropylene braid

Multipurpose product. Sold in reels.

Red	Blue	Green	Yellow	Ø mm	m
06.423.02RO	06.423.02BL	06.423.02VE	06.423.02GI	2	30
06.423.03RO	06.423.03BL	06.423.03VE	06.423.03GI	3	17
06.423.04RO	06.423.04BL	06.423.04VE	06.423.04GI	4	12

## Nylon braids



Available in 100-m reels, 100% nylon, for general applications on board, splicing, sewing, etc.

Code	Ø mm
06.439.01	0.5
06.439.02	1
06.439.03	1.5
06.439.04	2

## Spare braid for underwater rifles

Made of **stabilized polypropylene**. Sold in reels and not by the metre.

Ø mm			Colour	m
1.5	2	2.5		
06.409.15	06.409.20	06.409.25	Black	500

OSCULATI



## Rubbing strakes

AISI 316

To prevent mooring line chafing. Made of polished AISI316 stainless steel. Moulded and tapered.

Code	Length mm	Width mm
06.361.50	150	20
06.361.60	200	20
06.361.70	300	20
06.361.80	450	20
06.361.90	650	20
06.361.96	960	20
06.362.70	300	25
06.362.80	450	25
06.362.90	610	25



OSCULATI




## D-shape profile

AISI 316

Rubbing strake to prevent mooring line chafing. Precision casting. Hidden-stud mounting.

Code	Length mm	Width mm	Height mm	Stud Ø mm
06.368.30	300	15	15	5



## Adhesive anti-chafe SS sheets

Extra flexible stainless steel sheets to protect boat gelcoat and paint against any damage caused by rope chafing. Suitable to protect from chafing caused both by mooring and manoeuvring lines. Made of stainless steel and provided with 3M VHB™ powerful adhesive tape. Gelcoat and paint are preserved.

Code	Dimensions mm	Sheet No.	Material
06.313.15	150 x 50	1	SS
06.313.22	225 x 50	1	SS

