

GP 5 inflator

Supplied with compatible adapter to suit most valve types.

Code	Type	Max pressure	Tank	Pressure gauge	\longleftrightarrow mm
66.446.77	GP 5	400 mbar	5 l	No	210x290x80

**Two chamber professional Foot Pump BRAVO 10**

Worldwide patent No. 21847. The double chamber enables reaching the recommended pressure of large fabric or rubber dinghies effortlessly.

Fitted with visual pressure indicator, crushproof hose and three inflating connections. Equipped with deflation device.

Code	Twin chamber	Max pressure	Tank		Pressure switch	\longleftrightarrow mm
			chamber 1	chamber 2		
66.446.50	Yes	800 mbar	5.5 l	1.6 l	Yes	350x250x80

**Electric inflator pumps****Electric inflator for dinghies and SUP boards**

2-stage pump for inflation and deflation.

Compact and easy to carry by means of a comfortable handle.

Digital controller and LCD display for pressure setting.

Lighter plug + battery clamps.

Code	Function	V	W	Flow l/min	Max pressure	Current draw A	\longleftrightarrow mm
66.451.01	Inflation + deflation	12	110	350 at low pressure 70 at high pressure	1380 mbar (20 PSI)	9-12	155x250x175

**GE BP-1 12V inflator**

Automatic stop when the adjustable preset pressure is reached.

With a flow of **160 l/min**, it inflates at a max pressure of **1200 mbar (18 psi)**.

The hose/inflator screw-type connector is stable and safe.

It comes in a shoulder carrying bag with all accessories: 1.7-m hose, 3-m power cable, lighter plug and 12V battery clamps.

The standard version with bayonet fitting is ideal for **SUP** boards.

Code	Functions	V	W	Flow l/min	Max pressure	Current draw A	\longleftrightarrow mm	OPTIONAL connections
66.449.11	Inflation	12	240	160	1200 mbar (18 PSI)	13	205x105x130	66.449.12

66.449.12 The spares kit includes an additional hose and several fittings to inflate kits, dinghies, liferafts, air mattresses and pool inflatables.

**GE BTP-1 inflator**

Automatic stop when the preset pressure, adjustable by means of a pressure gauge, is reached. Fitted with air filter, it comes with a bag, 1.7-m hose, 3-m supply cable, compatible fittings, lighter plug and 12V battery clamps.

Code	Functions	V	W	Flow l/min	Max pressure	Current draw A	\longleftrightarrow mm
66.449.04	Inflation+deflation	12	240	120-420	1000 mbar (14.5 PSI)	13	295x105x160

