

**Male connection made of brass**

Code	For fitting on	ORDER BY BOX
14.236.45	14.235.20; 14.235.40; 14.235.60	50

**Female connection made of brass**

Code	For fitting on	ORDER BY BOX
14.236.46	14.235.10; 14.235.30; 14.235.50	100

**Silicone nipple for watertight closure**

Code	For cable size mm <sup>2</sup>	ORDER BY BOX
14.236.48	0,5/1,5	100

**Watertight connectors for cables up to 10 mm<sup>2</sup>****Watertight connectors**

A complete connector consists of item numbers: connector + 2 Faston male terminals 14.231.20/40 + 2 Faston female terminals 14.231.0/30 + 4 inserts with seals of suitable section 14.232.01/02.

Code	Version	For cable size mm <sup>2</sup>
14.231.10	Faston female	4/6
14.231.20	Faston male	4/6
14.231.30	Faston female	8/10
14.231.40	Faston male	8/10
14.232.01	Plug with gasket	4/6
14.232.02	Plug with gasket	8/10



▲ 14.232.01



▲ 14.232.01-02



▲ 14.231.10/30



▲ 14.231.20/40

**BULGIN BUCCANEER plugs and sockets**

RINA type-approved, managed polarity, 100% watertight, IP 68 protection degree. Fibreglass-reinforced nylon body, nickel-plated brass contacts, watertight screw-in cap, type-approved in compliance with NATO military standards. Operating temperature range - 20°+ 70°.

**Male contact plug**

Flying plug to pair with a female contact socket.

Code	Poles	Capacity
14.350.02	2	10 A
14.350.03	3	10 A
14.350.09	9	5 A

**External socket, female contacts**

Includes watertight cover.

Code	Poles	For coupling to
14.360.02	2	14.350.02
14.360.03	3	14.350.03
14.360.09	9	14.350.09

**Built-in socket, female contacts**

Includes watertight cover.

Code	Poles	For coupling with
14.370.02	2	14.350.02
14.370.03	3	14.350.03
14.370.09	9	14.350.09

