

Inspection hatches, type-tested in compliance with Directive 2013/53/UE



▲ 20.840.00 / 20.844.00



▲ 20.840.50

Inspection hatch with cover, CE approved

Antiskid **watertight** surface, recess hole with swivelling hollow flat. It can be installed on any sports craft, boat design category A, B, C, and D, area II a, III, IV, watertightness degree 2.

White	Cream RAL 9001	Black	Grey	Max external Ø mm	Passage mm	Recess Ø mm	Hole centre distance mm
20.840.00	20.840.40	20.840.50	20.840.60	265	190	215	242
20.844.00	-	20.844.50	-	315	240	270	290



▲ 20.840.40



▲ 20.840.60

CE APPROVED
based on
UNI EN ISO 12216:2004



Hatch fitted with hidden screws and cam cover locking

Code	Max outer Ø mm	Inner Ø mm	Recess mm
20.845.00	325	240	290

Easy opening inspection hatches

Screw locking, **watertight**, equipped with rubber O-RING; fitted with ridge for easy opening (non flush).



Code	Outer Ø mm - A	Opening Ø mm - B	Color
20.201.00	145	100	<input type="checkbox"/> white
20.202.00	170	127	<input type="checkbox"/> white
20.203.00	206	155	<input type="checkbox"/> white



Polypropylene Inspection hatches, fitted with hidden mounting screws

Screw-locking, 100% watertight, equipped with rubber O-RING



▲ 20.199.01/02/03



▲ 20.199.11/12/13

White	Black	External Ø mm	Opening Ø mm
20.199.01	20.204.20	160	102
20.199.02	20.199.12	182	127
20.199.03	20.199.13	220	152

Stylish and practical EC type-approved inspection hatch.

Screw turning lock, 100% watertight, fitted with rubber O-RING.



▲ 20.205.00;20.204.00;20.206.00;20.207.00




▲ 20.205.01;20.204.01;20.206.01;20.207.01

Polypropylene			Clear with white ring nut	Outside Ø mm	Opening Ø mm
white	black	Grey RAL 7042			
20.204.00	20.204.20	20.204.30	20.204.01	147	102
20.206.00	20.206.20	20.206.30	20.206.01	172	125
20.205.00	20.205.20	20.205.30	20.205.01	205	152
20.207.00	20.207.20	20.207.30	20.207.01	260	203



▲ 20.205.20;20.204.30;20.206.20;20.207.20



▲ 20.205.30;20.204.30;20.206.30;20.207.30

CE APPROVED
based on
UNI EN ISO 12216:2004