Stainless steel rollers

Bow roller for dolphin strikers

Made of stainless steel for mounting under the dolphin striker.

| Code | Sheave material | Recess fit width mm | Spare sheave 01.219.94 | |
|-----------|-----------------|---------------------|---------------------------|--|
| 01.119.92 | Hard rubber | 85 | | |
| | | - 97 - | 85 200 142 | |





Bow roller, compact version

Made of satin-finish stainless steel with nylon sheave.

| Code | Length mm | Width mm | Height mm | Spare sheave |
|-----------|-----------|----------|-----------|--------------|
| 01.118.82 | 155 | 51 | 72 | 01.218.82 |
| | | | | |

101

Bow fairlead

Very sturdy and practical, made of AISI316 stainless steel, nylon sheave suitable for ropes up to 14 mm and for chains up to 6/8 mm. Product by Osculati.

| Code | Length mm | Base mm |
|-----------|-----------|---------|
| 01.349.00 | 130 | 90x90 |

Bow roller with safety pin

Made of satin-finish stainless steel. Hard rubber sheave.


| Code | Length | Width with safety pin | Spare | Anchor max weight kg | Max Ø | |
|-----------|-----------|------------------------------------|-------------|-------------------------|------------------|----------|
| | mm | mm | sheave | | line mm | chain mm |
| 01.118.83 | 280 | 55 | 01.218.82 | 15 | 24 | 10 |
| 01.118.91 | 231.5 | 51 | 01.218.82 | 15 | 24 | 10 |
| | 16:811:10 | 231,5 - 231,5 - 93 - 138,5 - | ▲ 01.118.83 | -12- 106 | -* 280 174 | |


01.118.83 01.118.91


Bow roller with fairlead

Made of satin-finish stainless steel, suitable for mounting over or under the dolphin striker.

| Code | Length mm | Width mm | Spare sheave |
|-----------|-----------|----------|--------------|
| 01.118.86 | 393 | 52 | 01.218.82 |
| 01.119.94 | 500 | 84 | 01.219.94 |
| 01.119.95 | 588 | 98 | 01.219.95 |







Bow rollers for small vessels

AISI 316 Mirror-polished stainless steel with thermopolymer sheave.

| Code | Length mm | Width mm | Height mm | Spare sheave |
|-----------|-----------|----------|-----------|--------------|
| 01.118.80 | 205 | 45 | 53 | 01.346.51 |

