CISCULATI









▲ 11.413.11

▲ 11.413.12

⊿11.413.13 **▲** 11.413.14





▲ 11.413.15

▲ 11.413.03

▲11.413.05

Utility Compact navigation lights for deck mounting

RINA type-approved in compliance with COLREG72 standards. Suitable for vessels up to 12 metres. Powered by a small high intensity 5W bulb for very compact size, minimum heat and low current draw. 2-screw mounting.

Туре	Body		Bulb			
	white	black	halogen, included		LED OPTIONAL*	
112,5° left	11.413.11	-	14.412.00	(12 V - 5 W)	14.225.01	
112,5° right	11.413.12	-	14.412.00	(12 V - 5 W)	14.225.01	
225° bow	11.413.13	11.413.03	14.412.00	(12 V - 5 W)	14.225.01	
135° stern	11.413.14	-	14.412.00	(12 V - 5 W)	14.225.01	
112,5° + 112,5° bicolor	11.413.15	11.413.05	14.412.00	(12 V - 5 W)	14.225.01	

Not certified, with LED bulb.

OSCULATI







▲ 11.425.01



▲ 11.415.01

▲ 11.425.04





▲ 11.425.05



▲ 11.415.02



▲ 11.415.02

Utility 77 navigation lights

Type-approved lights for vessels up to 12-m long. RINA type-approval in compliance with the COLREG72 regulations. Recommended for medium size boats, 100% watertight, easy to install. Supplied with lamp sockets and bulbs.

Туре	Body		Granted	Bulb		
	white	black	visibility	halogen, included		LED OPTIONAL*
112.5° left	11.425.01	11.415.01	up to 1 mile	14.300.00	(12 V - 10 W)	14.301.22
112.5° right	11.425.02	11.415.02	up to 1 mile	14.300.00	(12 V - 10 W)	14.301.22
225° bow	11.425.03	11.415.03	up to 2 miles	14.300.00	(12 V - 10 W)	14.301.22
135° stern	11.425.04	11.415.04	up to 2 miles	14.300.00	(12 V - 10 W)	14.301.22
112,5° + 112,5° bicolor	11.425.05	11.415.05	up to 1 mile	14.300.00	(12 V - 10 W)	14.301.22

Not certified, with LED bulb.






▲ 11.415.03



▲ 11.415.04



▲ 11.415.05



OSCULATI









11.414.01



11.414.02



11.414.03



11.414.04





11.414.05

Utility 85 navigation lights made of stainless steel

AISI 316

Lights made of mirror-polished stainless steel. RINA type-approved in compliance with the COLREG72 regulations.

Code	Туре	Halogen			
		bulb included		LED OPTIONAL*	
11.414.01	112.5° left	14.300.00	(12 V - 10 W)	14.301.22	
11.414.02	112.5° right	14.300.00	(12 V - 10 W)	14.301.22	
11.414.03	225° bow	14.300.00	(12 V - 10 W)	14.301.22	
11.414.04	135° stern	14.300.00	(12 V - 10 W)	14.301.22	
11.414.05	112.5° + 112.5° bicolor	14.300.00	(12 V - 10 W)	14.301.22	

Not certified, with LED bulb.

